

A d d e n d u m

Iowa Department of Transportation
Office of Contracts

Date of Letting: May 15, 2012
Date of Addendum: May 4, 2012

B.O.	Proposal ID	Proposal Work Type	County	Project Number	Addendum
005	45-C045-064	Bridge Replacement - CCS	Howard	BROS-C045(64)--8J-45	15may005.a01

Notice: Only the bid proposal holders receive this addendum and responsibility for notifying any potential subcontractors or suppliers remains with the proposal holder.

Attached is a SCHEDULE OF PRICES for the following items:

Line No. 0210 2599-9999009 EARTH CORING

Line No. 0220 2599-9999009 ROCK CORING

Bid these items as instructed and submit the bid for these items with the Bid Proposal.

Make the following changes to the PROPOSAL SCHEDULE OF PRICES:

Delete Line No. 0090 2501-6335010 PREBORED HOLES

If the above changes are not made on the proposal form, they will be made as shown here.

Make the following change to the plan:

SHEET 2 OF 6:

Add the following note to the reference notes for the item 2599-9999009, Earth Coring:

Reference Note #21 – 6 each for North abutment at 10.67 feet. 6 each for South abutment at 9.17 Feet. The price for this item shall include all costs associated with earth coring (or drilling) the holes from the bottom of the footing to the top of the rock, maintaining the open holes and furnishing and placing bentonite. Coring shall be 18 inch diameter (minimum). Method of maintaining holes shall be approved by the engineer. Method of measurement and basis of payment shall be based on the unit price per linear foot and shall be measured from the bottom of footing to the top of rock. Measurements shall be to the nearest tenth of a foot, as measured by the engineer. See sheet 6 for log of soil borings.

Make the following change to the plan:

SHEET 2 OF 6:

Add the following note to the reference notes for the item 2599-9999009, Rock Coring:

Reference Note #22 – 6 each for the North abutment at 4.33 feet. 6 each for the South abutment at 5.83 feet. 11 each for North pier at 15 feet. 11 each at South pier at 15 feet. The price for this item shall include all costs associated with rock coring (or drilling) the holes from the top of the rock to the specified depth, maintaining the open holes, and furnishing and placing concrete. Coring shall be 18 inch diameter (minimum). Method of maintaining holes shall be approved by engineer. Method of measurement and basis of payment shall be based on the unit price per linear foot and shall be measured from the top of rock to final approved depth. Measurement shall be to the nearest tenth of a foot, as measured by the engineer. See sheet 6 for log of soil borings.

Proposal ID No.: 45-C045-064
 Primary Work Type: BRIDGE REPLACEMENT - CCS
 Primary County: HOWARD

Bid Order No.: 005
 Letting Date: May 15, 2012
 10:00 A.M.

ITEMS LISTED ON THIS PAGE ARE ADDED BY ADDENDUM 15may005.a01

UNIT BIDS MUST BE TYPED OR SHOWN IN INK OR THE BID WILL BE REJECTED.

Line No	Item Number Item Description	Item Quantity and Unit	Unit Price		Bid Amount	
			Dollars	Cts	Dollars	Cts
Section 0001 (continued)						
ITEMS FOR A 120'-0 X 30'-6 CONTINUOUS CONCRETE SLAB BRIDGE						
0210	2599-9999009 EARTH CORING	119.000 LF	.		.	
0220	2599-9999009 ROCK CORING	391.000 LF	.		.	
Total Bid			.		.	