

# A d d e n d u m

Iowa Department of Transportation  
Office of Contracts

Date of Letting: March 19, 2013  
Date of Addendum: March 6, 2013

<b>B.O.</b>	<b>Proposal ID</b>	<b>Proposal Work Type</b>	<b>County</b>	<b>Project Number</b>	<b>Addendum</b>
603	78-0801-347	Bridge Cleaning	Pottawattamie	BRFN-030-1(132)--39-43 IMN-080-1(347)0--0E-78	19mar603.a01

---

Notice: Only the bid proposal holders receive this addendum and responsibility for notifying any potential subcontractors or suppliers remains with the proposal holder.

---

Make the following change to the PROPOSAL:

For Harrison County Project No. BRFN-030-1(132)--39-43:

REPLACE the attached proposal attachment SHEET 2 OF 3.

For Pottawattamie County Project No. IMN-080-1(347)0--0E-78:

REPLACE the attached proposal attachment SHEET 2 OF 4.

**For Bridge No. 4300.0S030:**

**Modify the Iowa Department of Transportation Standard Specifications for Highway and Bridge Construction, Series 2012, Section 2427, Bridge Cleaning, as follows:**

**Section 2427.01** Eliminate the first sentence and replace with the following:

"Remove all accumulated foreign material from the following areas:

- a. All steel, including inspection walkways and ladders, within 25 feet of expansion joints on the steel unit.
- b. Deck drain inlets and drain pipes.
- c. Top of modular and strip seal joints (care shall be taken not to dislodge box seals and glands in the deck). The bottom of the modular joints including the boxes that contain the joint bearings.
- d. All steel, including inspection walkways and ladders, within 25 feet of the center pier in the steel unit.
- e. Bird nests and adjacent droppings throughout the entire steel unit.
- f. Shoulder areas of the bridge deck.
- g. Abutment bridge seats.
- h. Pier tops below expansion joints at Piers 4, 9, 10, 11.

It also includes washing these elements with water under pressure."

**Section 2427.03B3** Eliminate the first sentence of the first paragraph and replace it with the following:

"Prior to cleaning with water pressure, remove all accumulated foreign material from the superstructure."

**For Bridge No. 7800.0L080 and 7800.0R080:****Modify the Iowa Department of Transportation Standard Specifications for Highway and Bridge Construction, Series 2012, Section 2427, Bridge Cleaning, as follows:**

**Section 2427.01** Eliminate the first sentence and replace with the following:

"Remove all accumulated foreign material from all weathering steel and all bearings."

- a. All steel, including inspection walkways and ladders, within 15 feet of an expansion joint.
- b. Abutment seats and adjacent piers within 15 feet of an expansion joint.
- c. Bird nests & adjacent droppings throughout the entire bridge
- d. Shoulder area of the bridge deck.
- e. Deck drain inlets and drain pipes.
- f. Neoprene drain troughs beneath finger expansion joints.
- g. Connection area of overhead sign trusses to girders.

It also includes washing these elements with water under pressure."

**Section 2427.03B#** Eliminate the first sentence of the first paragraph and replace it with the following:

"Prior to cleaning with water pressure, remove all accumulated foreign material from the superstructure."