

# A d d e n d u m

Iowa Department of Transportation  
Office of Contracts

Date of Letting: May 21, 2013  
Date of Addendum: May 2, 2013

<b>B.O.</b>	<b>Proposal ID</b>	<b>Proposal Work Type</b>	<b>County</b>	<b>Project Number</b>	<b>Addendum</b>
213	52-3806-257-A	PCC Patching	Johnson	IMN-380-6(257)0--0E-52	21may213.a02

---

Notice: Only the bid proposal holders receive this addendum and responsibility for notifying any potential subcontractors or suppliers remains with the proposal holder.

---

Make the following changes to the PROPOSAL SCHEDULE OF PRICES:

ADD Proposal Line No. 0100 2303-0063502, HOT MIX ASPHALT MIXTURE (30,000,000 ESAL), SURFACE COURSE, ½ IN. MIX, FRICTION L-2; 40.000 TONS

ADD Proposal Line No. 0110 2303-0247022, ASPHALT BINDER, PG 70-22; 2.400 TONS

ADD Proposal Line No. 0120 2527-9263109, PAINTED PAVEMENT MARKING, WATERBORNE OR SOLVENT BASED; 2.000 STA.

If the above changes are not made, they will be made as shown here.

Add the following to the PLAN SHEET C.1, ESTIMATE REFERENCE INFORMATION, TAB 100-4A:

ITEM 2303-0063502 HOT MIX ASPHALT MIXTURE (30,000,000 ESAL), SURFACE COURSE, ½ IN. MIX, FRICTION L-2: This item is for placement of HMA overlays on the approaches to the bridges over 33<sup>rd</sup> Avenue, northbound and southbound, near and far approaches, at milepost 17.6. Each overlay is estimated at 52 feet in width x 20 feet in length x 1.5 inches in thickness. The purpose of the overlays is to level the bridge approaches to provide smooth transitions to and from the bridge decks. The overlay thicknesses shall vary as needed to provide smooth transitions. The overlays shall terminate with full run outs. Construction of milled surface notches is not intended. A sand seal shall be placed on each run out. Refer to Article 2307.03.B.6 for sand seal application rates. The unit price shall include: cleaning and preparation of the existing surface prior to placing the overlays, placement of a tack coat, and placement of the sand seal.

ITEM, 2303-0247022, ASPHALT BINDER, PG 70-22: The quantity is estimated at 6% of the Hot Mix Asphalt Mixture quantity.

ITEM, 2527-9263109, PAINTED PAVEMENT MARKING, WATERBORNE OR SOLVENT BASED: The quantity includes 0.8 Sta. of 4" white edge line, 0.8 Sta. of 4" yellow edge line, and 1.6 Sta. of 4" broken white lane line.