

Dynamic Speed Feedback Signs for Rural Traffic Calming

Authors

Shauna L. Hallmark

Interim Director, Institute for Transportation, and Professor, Civil, Construction, and Environmental Engineering, Iowa State University
515-294-5249, shallmar@iastate.edu

Skylar Knickerbocker

Researcher, Institute for Transportation, Iowa State University

Neal Hawkins

Director, Center for Transportation Research and Education, Iowa State University

Sponsors

Iowa Highway Research Board
Iowa Department of Transportation
Midwest Transportation Consortium
Federal Highway Administration
(IHRB Project TR-630, InTrans Project 11-393)

For More Information

www.intrans.iastate.edu/



Center for Transportation Research and Education
Iowa State University
2711 S. Loop Drive, Suite 4700
Ames, IA 50010-8664
515-294-8103



Center for Transportation
Research and Education

IOWA STATE UNIVERSITY

Institute for Transportation

Background

Small rural communities often lack the expertise and resources necessary to address speeding and the persistent challenge of slowing high-speed through traffic. The entrances to communities are especially problematic given that drivers must transition from a high-speed, often-rural roadway setting to a low-speed community setting.

The rural roadway provides high-speed mobility outside the community, yet the same road within town provides local access and accommodates pedestrians of all ages, on-street parking, bicycles, and other features unique to the character of a small community. Drivers who have been traveling for some distance on the high-speed road, and are traveling through the community, may not receive the appropriate clues that the character of the roadway is changing and may not adjust their speeds appropriately.

Addressing speeding issues is an even greater challenge given that smaller communities typically lack engineering staff and resources, which can lead

to decisions that may not conform to accepted design guidance. For instance, many rural communities set speed transition zones too low a significant distance outside the community, before there is any practical need for drivers to slow down.

Communities may also have unrealistic expectations about what speed reductions are practical and, in some cases, may even implement strategies to reduce speeds that are not appropriate for the situation. For instance, some small communities with speeding issues simply use stop signs to slow traffic, which can diminish both enforcement and compliance.

A number of traffic-calming devices were evaluated to determine their effectiveness in reducing speeds along the main road through a small rural community. Five different treatments were selected and installed in six rural Iowa communities. This tech brief highlights use of two different dynamic speed feedback signs (DSFSs).



DSFS installed at Rowley east community entrance

Description

Dynamic speed feedback signs consist of a speed-measuring device, which may be a loop detector or radar, and a message sign that displays feedback to drivers who exceed a predetermined speed threshold. The feedback may be the driver's actual speed, a message such as SLOW DOWN, or activation of some warning device, such as beacons or a curve-warning sign, when a vehicle exceeds a certain speed. The devices can be portable or permanent. They alert drivers that they are speeding and create a sense of being monitored to the driver. They may also slow drivers who have radar detectors.

The Texas Transportation Institute (TTI) evaluated the use of a portable speed display trailer in work zones (Fontaine et al., 2000). The researchers found that passenger vehicle speeds were reduced by 7 to 9 mph at one site and 2 to 3 mph at another. Truck speeds were reduced 3 to 10 mph at both sites.

The Department of Transport, United Kingdom, found that average speeds can be reduced by 1 to 7 mph using dynamic speed signs; they also suggest that signs are more effective on a mobile basis, given drivers may become immune when the signs are installed on a permanent basis (Sustrans, 2005).

Chang et al. (2004) tested the use of radar speed signs in reducing speeds and found the devices were effective and had a sustained effect in maintaining lower 85th percentile and average speeds.

Two different signs were evaluated as part of the previous traffic-calming research project by Hallmark et al. (2007). One sign technology involving displaying the current speed of the driver in Union, Iowa was effective at reducing speeds significantly. Another sign was evaluated in Slater, Iowa that was capable of providing different messages to the driver in addition to their current speed. The sign reduced the average speed of the drivers by 5 mph and the 85th percentile speed by 7 mph.



Radar-activated LED speed limit sign

Treatment Installation

Two different DSFSs were used. The first was a speed limit sign that has radar-activated light-emitting diodes (LEDs) embedded around the border of the sign. One radar-activated LED speed limit sign was placed at the east community entrance along State Highway 251/West Main Street in St. Charles, Iowa. The second was placed at the west community entrance on County Road D-47 in Rowley, Iowa. The signs were programmed so that the LEDs activated when vehicles were traveling over the mean speed, which was established in a before speed study.

The second DSFS evaluated was a sign that displayed vehicle speed. The sign activated when vehicles were traveling over the mean speed, which was established during a speed study before installation of the sign. This sign does not display over 55 mph so that drivers are not tempted to “test” their speeds against the sign. The sign was placed on County Road D-47 at the east community entrance in Rowley, Iowa.

Results

Pneumatic road tubes were used to collect speed and volume data before and after installation of the rural traffic-calming treatments. Pneumatic road tubes are fairly accurate (99 percent accuracy for individual vehicle speeds), can collect individual vehicle data (speed, volume, headway, and classification), and are fairly low-cost. Data were collected using JAMAR FLEX HS counters. Road tubes were typically laid just downstream of the treatment or at the treatment.

Data were typically collected for 48 hours on a Monday through Friday under mostly dry weather conditions. In a few cases, due to issues with the traffic counters, data were available for only a 24 hour period. Use of full 24 hour periods avoids biasing the speed sample to speed choices based on time of day. The collection periods occurred Monday through Friday while avoiding holidays to avoid any unusual traffic patterns.

Typical speed statistics, such as change in average speed, were calculated for each location where data were collected as described below.

Speeds decreased at both sites with the radar-activated LED sign. Only a minor decrease occurred at the St. Charles site with a -0.4 mph decrease in mean speed and no change in the 85th percentile speed. Decreases of about 10 percent in the fraction of vehicles traveling 5 or 10 mph over the posted speed limit resulted for that site with no statistically-significant changes for vehicles traveling 15 or 20 mph over the speed limit.

The second radar-activated LED sign, located in Rowley, had large decreases in both mean and 85th percentile speeds (a decrease of 6 and 7 mph, respectively). Large decreases were also noted for vehicles traveling over the speed limit by a certain threshold with a 25 decrease in the fraction of vehicles traveling 5 mph over, a 40 percent decrease for vehicles traveling 10 mph over, a 53 percent decrease for vehicles traveling 15 mph over, and a 65 percent decrease in the fraction of vehicles traveling 20 or more mph over.

The speed display sign had similar large decreases with reductions of 8 and 9 mph in mean and 85th percentile speeds, respectively. The fraction of vehicles traveling 5 or more mph over the posted speed limit decreased by about 45 percent and the fraction of vehicles traveling 10 or more mph over decreased by 73 percent. A decrease of about 80 percent resulted in both the fraction of vehicles traveling 15 or more mph over and 20 or more mph over the posted speed limit.

Results for speed feedback sign treatment at 1 month after installation

	St. Charles LED	Rowley LED	Rowley Speed Sign
Mean Speed	-0.4	-5.9	-7.6
85th Percentile Speed	0	-7	-9
Fraction of Vehicles Traveling Over Posted Speed Limit			
≥ 5 mph	-8.70%	-25.30%	-45.20%
≥ 10 mph	-11.10%	-40.30%	-73.40%
≥ 15 mph	25.0%*	-52.90%	-78.90%
≥ 20 mph	0.0%*	-64.50%	-80.00%

* Not statistically significant at 95% level of significance

References

Chang, Kevin, Matthew Nolan, and Nancy L. Nihan. 2004. Radar Speed Signs on Neighborhood Streets: An Effective Traffic Calming Device. 2004 ITE Annual Meeting and Exhibit Lake Buena Vista, FL. August 2004.

Fontaine, Michael, Paul Carlson, and Gene Hawkins. 2000. *Evaluation of Traffic Control Devices for Rural High-Speed Maintenance Work Zones: Second Year Activities and Final Recommendations*. FHWA/TX-01/1879-2. Texas Transportation Institute. Texas Department of Transportation.

Hallmark, Shauna L., Eric Peterson, Eric Fitzsimmons, Neal Hawkins, Jon Resler, and Tom Welch. 2007. *Evaluation of Gateway and Low-Cost Traffic-Calming Treatments for Major Routes in Small Rural Communities*. November 2007. www.intrans.iastate.edu/research/detail.cfm?projectID=-226410767

Sustrans. Rural Minor Road Traffic Calming. National Cycle Network, College Green, Briston, UK. www.sustrans.org.uk. Accessed February 2005.

About the Center for Transportation Research and Education

The mission of the Center for Transportation Research and Education (CTRE) at Iowa State University is to develop and implement innovative methods, materials, and technologies for improving transportation efficiency, safety, reliability, and sustainability while improving the learning environment of students, faculty, and staff in transportation-related fields.

The sponsors of this research are not responsible for the accuracy of the information presented herein. The conclusions expressed in this publication are not necessarily those of the sponsors.

Iowa State University does not discriminate on the basis of race, color, age, religion, national origin, sexual orientation, gender identity, genetic information, sex, marital status, disability, or status as a U.S. veteran. Inquiries can be directed to the Director of Equal Opportunity and Compliance, 3280 Beardshear Hall, (515) 294-7612.