

# A d d e n d u m

Iowa Department of Transportation  
Office of Contracts

Date of Letting: January 20, 2016  
Date of Addendum: January 5, 2016

<b>B.O.</b>	<b>Proposal ID</b>	<b>Proposal Work Type</b>	<b>County</b>	<b>Project Number</b>	<b>Addendum</b>
165	66-2189-118	HMA PAVEMENT WIDENING / HMA RESURFACING	MITCHELL	MB-218-2(500)69--77-66 STPN-218-9(118)--2J-66	20JAN165.A01

Make the following change to the plans.

STPN-218-9(118)--2J-66

ESTIMATE REFERENCE INFORMATION: SHEET NUMBER C.2

Item Codes 2320-0041500, 2303-0042500, 2303-0043504, 2303-0245828 and 2303-6911000.

Standard Specification Article 2303.02, D, 7 shall be amended to the following:

7. Prepare gyratory mixture designs following the procedure outlined in Materials I.M. 510. Submit a mixture design complying with Materials I.M. 510. The JMF shall not exceed 1.4% absorbed asphalt (Pba) when calculated according to Materials I.M. 501. Propose both a production and a compaction temperature between 215°F (102°C) and 280°F (138°C) for WMA mixture designs.

The Engineer will calculate and exclude quantities of absorbed asphalt binder exceeding 1.4%.