Addendum

Iowa Department of Transportation Date of Letting: July 17, 2012
Office of Contracts Date of Addendum: June 21, 2012

B.O.	Proposal ID	Proposal Work Type	County	Project Number	Addendum
106	56-3942-615	PCC Sidewalk/Trail	Lee	SRTS-U-3942(615)8U-56	17jul106.a01

Notice: Only the bid proposal holders receive this addendum and responsibility for notifying any potential subcontractors or suppliers remains with the proposal holder.

Make the following change to the Plan Sheet S.09:

Replace: Tab. 113-10 SIDEWALK COMPLIANCE With attached: Tab. 113-10 SIDEWALK COMPLIANCE

Make the following change to the Plan Sheet S.10:

Replace: Tab. 113-10 SIDEWALK COMPLIANCE With attached: Tab. 113-10 SIDEWALK COMPLIANCE

Make the following change to the Plan Sheet S.11:

Replace: Tab. 113-10 SIDEWALK COMPLIANCE With attached: Tab. 113-10 SIDEWALK COMPLIANCE

96-22-11	SLOPES	Elevation	669.66	670.05	670.05	669.98	669.68	669.42	669.61	669.76	669.68		667.61	668.10	668.10	668.02		667.41	667.57	667.67	667.65	667.36	665.50	666.50	666.49	666.41	000.00		665.76	666.60	666.29	666.68	666.76	665.83		
	ONLY: DESIGNED S	_	0.00	\vdash	\top	-5.00		\top	\top	\Box	00.00		++-	0.00	-	\vdash		+	15.00	\vdash	+	$\overline{}$	\top	\top	\top	-5.00	\top	\neg	\vdash	-	0.00	$\overline{}$	-	+		
	FOR INFORMATION ONLY: USED TO DETERMINE DESIGN	Station	11+83.55	11+77.37	11+72.37	11+77.37	11+81.02	12+13.39	12+16.75	12+21.75	12+16.75		13+61.95	13+51.82	13+46.82	13+51.82		13+90.66	13+89.60	14+13.82	13+98.59	13+88.80	16+93.42	16+79.21	16+74.21	16+79.21			17+23.96	17+55.26	17+52.81	17+45.21	17+40.21	17+23.57		
	JES	Point	W1101 W1102	W1103	W1105	W1106	/01IM	W1201	W1202 W1203	W1204	W1205 W1206		W2101	W2102	W2103 W2104	W2105		+	W2202 W2203	\vdash	+		W3101	W3102	W3104	W3105	200	+	W3201	-	+	+	+	+		
SIDEWALK COMPLIANCE See S Sheets	Remarks																																			
							'									1 1							- 1					- 1 - 1				.	1		200%	-
	cceptable Range	Pos. or Neg.	1. 1.	.80% TO 2.00%	.80% 10 2.00%	00% TO 8.33%	.00% MAX. .80% TO 2.00%	.00% TO 8.33%	.80% TO 2.00%	.80% TO 2.00%	.00% TO 8.33%	.80% TO 2.00%	.00% TO 8.33%	.80% TO 2.00%	.80% TO 2.00%	.00% TO 8.33%	.80% TO 2.00%	.00% TO 8.33%	.80% TO 2.00%	.00% TO 5.00%	00% TO 8.33%		12	.80% TO 2.00%	일은	2	.80% TO 2.00%		.00% TO 8.33%	ୁଞ	.00% TO 8.33%	.80% TO 2.00%	.80% TO 2.00%	.00% MAX.	.80% TO .	
	Slope Acceptable Range	Pos. or	5 5	0.80% TO 2	0.80% 10 2 0.80% TO 2	1.00% TO 8	0.40 2.00% MAX. 1.50 0.80% TO 2.00%	1.00% TO 8	0.80% TO 2	0.80% TO 2	5.07 1.00% TO 8.33% 0.00 2.00% MAX.	0.80% TO 2	1.00% TO	1.50 0.80% TO 2.00%	0.80% TO	1.00% TO	0.80% TO 2.	1.00% TO	1.50 0.80% TO 2.00% 1 50 0.80% TO 2.00%	0.00% TO	1.00% TO 8	2.00% MAX. 0.80% TO 2.	1.00% TO	1.50 0.80% TO 2.00%	0.80% TO	1.00% TO	10 Z		1.00% TO	1.00% IO	4.05 1.00% TO 8.33%	0.80% TO	7.27 1.00% TO 2.00% 7.27 1.00% TO 8.33%	1.40 2.00% MAX.	1.50 0.80% TO 2	
	Slope	% Pos. or	1.00% TO 8	1.50 0.80% TO 2	1.50 0.80% 10 2 1.50 0.80% TO 2	7.69 1.00% TO 8	2.00% MAX. 0.80% TO 2	5.66 1.00% TO 8	1.50 0.80% TO 2	1.50 0.80% TO 2	1.00% TO 8 2.00% MAX.	1.50 0.80% TO 2	4.84 1.00% TO	0.80% TO	1.50 0.80% TO	4.06 1.00% TO	1.50 0.80% TO 2.	2.02 1.00% TO	1.50 0.80% TO	0.49 0.00% TO	2.96 1.00% TO 8	2.00% MAX. 0.80% TO 2.	7.04 1.00% TO	1.50 0.80% TO	1.50 0.80% TO	1.00% TO	1.50 0.80% TO 2		7.43 1.00% TO	0.40 2.00% IO	4.05	1.50	1.50	1.40	0.075 1.50 0.80% TO 0.075 1.50 0.80% TO 0.075	
		FT % Pos. or	5.95 1.00% TO 8 5.95 1.00% TO 8	0.075 1.50 0.80% TO 2	0.075 1.50 0.80% 10.2	0.30 7.69 1.00% TO 8	0.40 2.00% MAX. 1.50 0.80% TO 2	0.19 5.66 1.00% TO 8	0.075 1.50 0.80% TO 2	0.075 1.50 0.80% TO 2	5.07 1.00% TO 8 0.00 2.00% MAX.	0.075 1.50 0.80% TO 2	0.49 4.84 1.00% TO	1.50 0.80% TO	0.075 1.50 0.80% TO	0.33 4.06 1.00% TO	0.075 1.50 0.80% TO 2.	0.16 2.02 1.00% TO	0.075 1.50 0.80% TO	10.25 0.05 0.49 0.00% TO	0.075 1.50 0.80% 10.2 0.29 2.96 1.00% TO 8.	1.00 2.00% MAX. 1.50 0.80% TO 2.	1.00 7.04 1.00% TO	0.075 1.50 0.80% TO	0.075 1.50 0.80% TO	6.12 1.00% TO	0.075 1.50 0.80% TO 2		0.84 7.43 1.00% TO	0.33 4.28 1.00% O	0.31 4.05	0.075 1.50	0.075 1.50	0.07 1.40	1.50	
Does not include cumb	Δ Elevation Slope	FT FT % Pos. or	0.34 5.95 1.00% TO 8 0.05 5.95 1.00% TO 8	5.00 0.075 1.50 0.80% TO 2	5.00 0.075 1.50 0.80% 10 2 5.00 0.075 1.50 0.80% 10 2	0.30 7.69 1.00% TO 8	5.00 0.02 0.40 2.00% MAX. 5.00 0.075 1.50 0.80% TO 2	3.36 0.19 5.66 1.00% TO 8	5.00 0.075 1.50 0.80% TO 2	5.00 0.075 1.50 0.80% TO 2	0.26 5.07 1.00% TO 8 0.00 0.00 2.00% MAX.	5.00 0.075 1.50 0.80% TO 2	0.49 4.84 1.00% TO	5.00 0.075 1.50 0.80% TO	5.00 0.075 1.50 0.80% 10	0.33 4.06 1.00% TO	5.00 0.075 1.50 0.80% TO 2.	RAMP RUNNING SLOPE 7.94 0.16 2.02 1.00% TO	5.00 0.075 1.50 0.80% TO 5.00 0.075 1.50 0.80% TO	SIDEWALK RUNNING SLOPE 10.25 0.05 0.49 0.00% TO	PF 9.80 0.075 1.50 0.80% 10.22	5.00 0.05 1.00 2.00% MAX. 5.00 0.075 1.50 0.80% TO 2.	E 14.21 1.00 7.04 1.00% TO	5.00 0.075 1.50 0.80% TO	5.00 0.075 1.50 0.80% TO	E 13.90 0.85 6.12 1.00% TO	0.075 1.50 0.80% TO 2		RAMP RUNNING SLOPE 11.30 0.84 7.43 1.00% TO	RAMP RUNNING SLOPE /./2 0.33 4.28 1.00% 10 RAMP CROSS SLOPE 5.00 0.03 0.40 2.00% MA	RAMP RUNNING SLOPE 7.65 0.31 4.05	LANDING 5.00 0.075 1.50	LANDING 5.00 0.075 1.50 RAMP RINNING SIOPF 11.69 0.85 7.27	RAMP CROSS SLOPE 5.00 0.07 1.40	5.00 0.075 1.50 5.00 0.075 1.50	

	SLOPES	Elevation	666.82	666.90 668.47	666.97	66.25	0	60.86	661.43 667.96	64.42	661.28	660.77	61.60	661.67	663.1 / 661.57	560.83	661.64	662.28	662.36	662.35	40.104	61.45	662.03	62.03	661.95		
	V)	_	-5.00	\neg	0.00			-	0.00	+		-	+	+	5.00	-		П	Ť	0.00				Ħ	5.00		
	SMATION ERMINE	+	17+91.21	+	H			+	24+30.27	++			+	Н	25+21.27 25+21.27			H	+	27+86.28	+++			Н	28+34.28 28+23.22		
	ES		W3302	-	W3305 W3306		+++	W4101 W4102	+	W4106 W4107			+	+	W4205 W4206	+	++	H	_	W5105	+	++	W5202	+			
LK COMPLIANCE See S Sheets	Remarks																										
SIDEWALK see s																											
		53.7	- 10	% %	%0	%0		10° 60°	4 94 9	\$ 26 25	9 89 9		9 10	Ш	% %	94	24	200.	2.00%	33%	2000	32%	2.00%	200	.00%		
	Acceptable Range	Pos. or Neg.	.vv./ 10 6.55% .80% TO 2.00%	.80% TO 2.009 .00% TO 5.009	.80% TO 2.00	.00% MAX.	NV 14 1000	.00% MAX. .00% TO 8.33%	.00% TO 5.00%	.80% TO 2.00	.80% TO 2.00%	.00% TO 8.33%	.00% 10 2.00;	.00% TO 5.00%	.80% 10 2.00 .00% TO 8.33	.00% MAX.	.00% TO 8.33%	.80% TO 2.0	.80% 10 2	.00% TO 8.	.80% MAX.	.00% TO 8.	.80% TO	.80% TO 2	.00% TO 8. .00% MAX. .80% TO 2		
	Slope Acceptable Range		7.19 1.00% TO 8.55% 1.50 0.80% TO 2.00%			0.25 2.00% MAX. 1.50 0.80% TO 2.00%		1.00% MA 1.00% TO	5.00 0.00% TO 5.00% 4 96 0.00% TO 5.00%	0.80% TO	0.80% TO 0.80% TO 0.80% TO	1.00% TO	0.00%	0.00% TO	0.80% 10 1.00% TO	1.20 2.00% MAX. 2.00 0.80% TO 2.00	1.00% TO	0.80% TO	0.80% 10	1.00% TO	2.00 2.00% MAX. 1.50 0.80% TO 2.				3.80 1.00% TO 8.33% 1.60 2.00% MAX. 1.50 0.80% TO 2.00%		
	Elevation Slope	* 7	1.50	1.50	1.50			7.95 1.00% TO	0.00%	1.50 0.80% TO	7.45 1.00% TO 1.50 0.80% TO	7.64 1.00% TO	2.00 0.80% 10	5.00 0.00% TO	2.00 0.80% IO 7.98 1.00% TO	2.00% MAX. 0.80% TO 2	64 5.82 1.00% TO	1.50 0.80% TO	1.50 0.80% 10	7.32 1.00% TO	2.00% MAX. 0.80% TO 2	5.25	1.50	1.50			
	Δ Elevation Slope	FT %	0.075 1.50	0.075 1.50 1.50 5.00	0.075 1.50	0.25	0	0.02 0.40 2.00% MA 0.47 7.95 1.00% TO	1.53 5.00 0.00% TO	0.075 1.50 0.80% TO	7.45 1.00% TO 1.50 0.80% TO	0.70 7.64 1.00% TO	0.10 2.00 0.80% 10	1.50 5.00 0.00% TO	0.74 7.98 1.00% TO	1.20 2.00% MAX. 2.00 0.80% TO 2	0.64 5.82 1.00% TO	0.075 1.50 0.80% TO	0.075 1.50 0.80% 10	0.81 7.32 1.00% TO	2.00 2.00% MAX. 1.50 0.80% TO 2	0.58 5.25	0.075 1.50	0.075 1.50	3.80		
£	Sidewalk Designation Distance* A Elevation Slope	DINNING CLOSE 0 24 O GO 740	UNNING SLOPE 8:21 0.59 7.19 5.00 0.075 1.50	0.075 1.50 1.50 5.00	5.00 0.075 1.50	0.02 0.25 0.25 0.05 1.50	000	5.91 0.47 7.95 1.00% TO	5.00 0.10 2.00 0.80% IO PE 30.53 1.53 5.00 0.00% TO PF 20.41 1.46 4.96 0.00% TO	5.00 0.075 1.50 0.80% TO 5.00 0.40% TO 5.00 0.075 1.50 0.80% TO 5.00 0.40% TO 5.00% TO 5.	JNNING SLOPE 5.90 0.00 7.5 1.50 0.80% TO 5.00 0.075 1.50 0.80% TO	NING SLOPE 9.16 0.70 7.64 1.00% TO	5.00 0.10 0.10 0.80% TO	IG SLOPE 30.00 1.50 5.00 0.00% TO	LOPE 9.27 0.74 7.98 1.00% TO)PE 5.00 0.06 1.20 2.00% MAX. 5.00 0.10 2.00 0.80% TO 2	0.64 5.82 1.00% TO	5.00 0.075 1.50 0.80% T0	5.00 0.075 1.50 0.80% 10	E 11.07 0.81 7.32 1.00% TO	5.00 0.075 1.50 0.80% TO 2	SI OPF 11.04 0.58 5.25	5.00 0.075 1.50	5.00 0.075 1.50	LOPE 11.06 0.42 3.80 PE 5.00 0.075 1.50 1.50		
boes not include curb	Sidewalk Designation Distance* & Elevation Slope	DAMO DIMMINIO CIODE 0 21 0 60 7 10	KUNNING SLUPE 8.21 0.59 7.19 4G 5.00 0.075 1.50	LANDING	LANDING	5.00 0.075 1.50 5.00 0.075 1.50	ALCO CO C	RAMP CKOSS SLOPE 5.00 0.02 0.40 2.00% MA CKOSS SLOPE 5.01 0.47 7.05 1.00% TO RAMDING SLOPE 5.01 0.47 7.05 1.00% TO RAMDING SLOPE 5.01 0.47 7.05 0.00% TO RAMDING SLOPE 5.01 0.47 7.05 0.00% TO 0.00% TO	SLOPE 30.53 1.53 5.00 0.00% TO SLOPE 20.41 1.46 4.96 0.00% TO	ADDITION	LANDING SLOPE 5.00 0.10 2.00 0.086 TO LANDING SLOPE 5.00 0.075 1.50 0.80% TO LANDING 5.00 0.075 1.50 0.80% TO	RAMP RUNNING SLOPE 9.16 0.70 7.64 1.00% TO	CANDING 3.00 0.10 2.00 0.00% 0 1 1 1 1 1 1 1 1 1	SIDEWALK RUNNING SLOPE 30.00 1.50 5.00 0.00% TO	LANDING	5.00 0.06 1.20 2.00% MAX. 5.00 0.10 2.00 0.80% TO 2	RAMP RUNNING SLOPE 11.00 0.64 5.82 1.00% TO	LANDING 5.00 0.075 1.50 0.80% TO	LANDING	RAMP RUNNING SLOPE 11.07 0.81 7.32 1.00% TO	5.00 0.075 1.50 0.80% TO 2	RAMP RUNNING SLOPE 11.04 0.58	LANDING 5.00 0.075 1.50 1.50	LANDING 5.00 0.075 1.50	11.06 0.42 3.80 5.00 0.075 1.50		

96-22-11	LOPES	Elevation	664.84	665.26	665.41	665.33	664.85			665.30	665.84	665.77	665.69	20.000	665.83	666.26	666.43	666.34	665.78														
	IN ONLY:	Offset	Ħ	\top	$^{+}$	$^{+}$	0.00		П	T	Т	П	2.00	\top	П	T	Т	0.00	\top														
	FOR INFORMATION CNLY: USED TO DETERMINE DESIGNED SLOPES	Station	31+16.08	31+10.36	31+05-36	31+10.36	31+16.36			31+52.42	31+63 36	31+63.36	31+58.36	01+02.40	34+95.91	34+88.02	34+82.09	34+88.02	34+95.98														
	VALUES	Point	W6101	W6102	W6103	W6105	W6106			W6201	W6202	W6204	W6205	WOZOW WOZOW	W7101	W7102	W7104	W7105	W7106														
																																	-
ш	Remarks																																
COMPLIANC Sheets																																	
SIDEWALK COMPLIANCE See S Sheets																																	
	Acceptable Range	Doe on Nee	1.00% TO 8.33%	.80% TO 2.00%	.00% TO 5.00%	.00% TO 8.33%	2.00% MAX.	.80% TO 2.00%		.00% TO 8.33%	.80% 10 2.00%	.80% TO 2.00%	.00% TO 8.33%	0.80% TO 2.00%	1.00% TO 8.33%	.80% TO 2.00%	.80% TO 2.00%	.00% TO 8.33%	.00% MAX.	.00% 10 2.00%													
	Slope	34	7.36				0.20							1.50				7.04															-
	Δ Elevation	t	0.42	0.075	0.075	0.48	0.01	0.075		0.47	0.075	0.075	0.37	0.075	0.43	0.075	0.075	0.56	0.05	0.0.0													1
	Distance* A	13	5.71	2.00	200.00	5.97	5.00	2.00		5.94	2.00	5.00	2.00	2.00	7.89	5.93	5.93	7.96	2.00	00.00													
ę	Sidewalk Decienation		RAMP RUNNING SLOPE	LANDING	ANDING	RAMP RUNNING SLOPE	RAMP CROSS SLOPE	LANDING		RAMP RUNNING SLOPE	LANDING	LANDING	RAMP RUNNING SLOPE	LANDING	RAMP RUNNING SLOPE	LANDING	LANDING	RAMP RUNNING SLOPE	RAMP CROSS SLOPE	LANDING													
Does not include curb	Point to Point		W6102	W6103	W6105	W6106	W6101	W6105		W6202	W6203	W6205	W6206	W6205	W7102	W7103	W7105	W7106	W7101	COI/M													
	1 :		1,-1	2	2 4	2	W6106	2		=	7/2	4	202	W6202	15	2 2	3 4	W7105	واو	7										П			